







Pre-Crimped Wire Leads

Fast and cost-effective solution for prototyping

FCI Basics offers a range of pre-crimped leads with a standard cable of 300mm length in receptacle-to-receptacle configurations.



Product	Description	Wire Size	Plating	Crimped lead P/N	CTW terminal P/N	More info
 WireLock® 1.80mm	Crimped lead with Tin plated terminals	AWG22	Tin	10156402-002LF	10153126-4C2LF	Landing page Presentation Datasheet
 Multipitch® 1.25/1.50mm	Crimped lead with Tin plated terminals	AWG26	Tin	10161198-N0030YYLF	10157551-0P10LF	Landing page Presentation Datasheet
 Minitek® 2.00mm	Crimped lead with Tin plated and Gold plated terminals	AWG28	Tin	10164491-001LF	77138-T01LF	Landing page Presentation Datasheet
			Gold	10164491-002LF	77138-101LF	
		AWG24	Tin	10164490-001LF	10044403-T01LF	
			Gold	10164490-002LF	10044403-101LF	
 Dubox® 2.54mm	Crimped lead with Tin plated and Gold plated terminals	AWG 20	Tin	10164492-K0030TLF	76347-412LF	Landing page Presentation Datasheet
			Gold	10164492-K0030GLF	76347-312LF	
		AWG 24	Tin	10164492-M0030TLF	76347-401LF	
			Gold	10164492-M0030GLF	76347-301LF	
 MicroSpace™ 1.27mm	Crimped lead with Tin plated terminals	AWG 26-28	Tin	10162767-P0030YYLF	10141272-112LF	Landing page Presentation Datasheet
		AWG 24		10162767-M0030YYLF	10141272-113LF	
		AWG 22		10162767-L0030YYLF	10141272-111LF	
 Mini PV® 2.54mm	Crimped lead with Tin plated terminals	AWG 22-26	Tin	10161663-001LF	47217-000LF	Landing page Presentation Datasheet
		AWG 28-32		10161663-002LF	47213-000LF	

These are standard versions defined to support customer prototype activity, contact us for other configurations or for volume production.